

TYPICAL PROPERTIES:

Thickness: 3.0 mm
3.5 mm
4.7mm

Basis Weight (Lb./MSF): 180
235
250

Brightness: 97+

Flexural Rigidity: MD 49, 65, 67
(In/Lb.) CD 36, 44, 47

Edge Crush (Lb./In): 170+
190+
200+

Standard Sheets Sizes: 48" x 96"
Maximum Sheet Size: 96" x 120"
(Custom sizes available subject to
minimum run quantities.)

PLATFORM COMPATIBILITY :

UV Screen
UV Flatbed Digital

Please see your conVerd Media
Distributor for more information or
email: contact@conVerd.com

Toll free 888.977.5050
Free fax 888.777.5060

PRODUCT DESCRIPTION

Enviroboard™ MR (Moisture Resistant)



Designed for use in point of purchase and trade show graphics applications, Enviroboard™ MR is a bright white, printable on both sides, dimensionally stable, rigid FSC-certified board material.

The Enviroboard™ MR base is made from a blend of 10% PCW (Post Consumer Waste) and 90% FSC-certified fiber to achieve its sustainable fiber balance. It is also fabricated into a composite board with a repulpable yet durable water based adhesive system.

Enviroboard™ MR has even achieved independent certification of recyclability through the North Carolina State University - Dept. of Wood and Paper Science*.

Enviroboard™ MR is a fully recyclable product for maximum sustainability.

* A copy of this certificate can be downloaded from our website www.conVerd.com.

Choose conVerd. Your GREEN resource.



FSC
SCS-COC-002001

© 1996. FSC
The FSC logo identifies products from well-managed forests.

